



TYRE DATA BOOKLET

315/680-18 DHB

315/680-18 WH

2020 | 2021

CONTENTS:

1: INTRODUCTION

2: STATIC DIMENSIONS (DHB/WH)

3: DYNAMIC MEASUREMENTS (DHB)

4: DYNAMIC MEASUREMENTS (WH)

5: STATIC RADIAL DEFLECTION (DHB)



INTRODUCTION

INTRODUCTION

This document provides the user with technical information regarding several aspects of the tyre characteristics. The data was acquired using indoor testing methods on physical tyres.

For individual car fitments, usage guidelines and prescriptions for camber and pressure please refer to the relevant Pirelli Technical Booklet, which is included as part of this Pirelli Data Package.



STATIC MEASUREMENTS

Slick Tyres				
Size & Fitment	Nominal Weight	Max Width (C)	Circumference (πD)	Tread Width (Cb)
	(kilograms)	(mm)	(mm)	(mm)
315/680-18 DHB 18"x12.0J	10.9	328	2158	295

Wet Tyres				
Size & Fitment	Nominal Weight	Max Width (C)	Circumference (πD)	Tread Width (Cb)
	(kilograms)	(mm)	(mm)	(mm)
315/680-18 WH 18"x12.0J	12.7	321	2165	283



DYNAMIC MEASUREMENTS @ 2.0bar (29psi), CA 0.0°



315/680-18x12.0J DHB

LOADED RADIUS

		LOAD [kg]				
		150	300	450	600	750
SPEED [km/h]	20	339.1	335.0	330.8	326.6	322.4
	60	339.4	335.3	331.2	327.0	322.9
	100	339.8	335.7	331.6	327.6	323.5
	140	340.1	336.1	332.1	328.1	324.2
	180	340.5	336.6	332.7	328.8	324.9
	220	340.9	337.1	333.3	329.5	325.7
	260	341.2	337.6	333.9	330.2	326.5
	280					
	300					

ROLLING RADIUS

		LOAD [kg]				
		150	300	450	600	750
SPEED [km/h]	20	339.6	339.0	338.4	337.9	337.3
	60	339.6	339.0	338.5	337.9	337.3
	100	339.6	339.1	338.5	338.0	337.4
	140	339.8	339.2	338.6	338.1	337.5
	180	340.0	339.4	338.9	338.3	337.7
	220	340.3	339.8	339.2	338.6	338.1
	260	340.8	340.3	339.7	339.1	338.6
	280					
	300					





DYNAMIC MEASUREMENTS @ 2.0bar (29psi), CA 0.0°



315/680-18x12.0J WH

LOADED RADIUS

		LOAD [kg]				
		200	300	400	500	600
SPEED [km/h]	20	338.9		333.1		326.8
	60	339.4		333.4		327.2
	100	340.0		334.1		327.9
	140	341.0		335.2		328.9
	180	342.5		336.7		330.4
	220	344.2		338.3		332.2

ROLLING RADIUS

		LOAD [kg]				
		200	300	400	500	600
SPEED [km/h]	20	340.0		337.5		336.0
	60	340.0		337.4		336.1
	100	340.6		338.0		336.8
	140	341.6		339.1		337.8
	180	343.1		340.6		339.3
	220	344.7		342.2		341.1





DYNAMIC MEASUREMENTS @ 2.0bar (29psi), CA 0.0°



315/680-18x12.5J WH

LOADED RADIUS

		LOAD [kg]				
		200	300	400	500	600
SPEED [km/h]	20	339.1		333.5		327.4
	60	339.5		333.6		327.7
	100	340.0		334.2		328.3
	140	340.9		335.2		329.1
	180	342.2		336.8		330.9
	220	344.3		338.8		332.9

ROLLING RADIUS

		LOAD [kg]				
		200	300	400	500	600
SPEED [km/h]	20	338.3		335.8		334.5
	60	338.4		335.8		334.6
	100	338.9		336.3		335.1
	140	339.8		337.2		336.2
	180	341.1		338.8		337.7
	220	343.4		340.9		339.8






STATIC RADIAL DEFLECTION – 315/680-18x12.0J @ CA 0.0 ° DHB

Load [kg]	Inflation Pressure [bar]						
	2.6	2.4	2.2	2.0	1.8	1.6	1.4
0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25	0.7	0.7	0.8	0.8	0.8	0.9	1.0
50	1.4	1.4	1.5	1.6	1.7	1.8	2.0
75	2.0	2.2	2.2	2.4	2.5	2.7	2.9
100	2.7	2.8	3.0	3.2	3.3	3.6	3.9
125	3.4	3.5	3.7	3.9	4.2	4.5	4.8
150	4.0	4.2	4.4	4.7	5.0	5.3	5.8
175	4.6	4.9	5.1	5.4	5.8	6.2	6.7
200	5.3	5.5	5.8	6.2	6.6	7.1	7.7
225	5.9	6.2	6.5	6.9	7.3	7.9	8.6
250	6.5	6.8	7.2	7.6	8.1	8.8	9.5
275	7.1	7.5	7.8	8.4	8.9	9.6	10.4
300	7.7	8.1	8.5	9.1	9.7	10.4	11.3
325	8.3	8.7	9.2	9.8	10.4	11.3	12.2
350	8.8	9.3	9.8	10.5	11.2	12.1	13.1
375	9.4	10.0	10.5	11.2	11.9	12.9	14.0
400	10.0	10.6	11.1	11.8	12.7	13.7	14.9
425	10.5	11.2	11.7	12.5	13.4	14.5	15.8
450	11.1	11.7	12.4	13.2	14.1	15.3	16.6
475	11.7	12.3	13.0	13.9	14.9	16.1	17.5
500	12.2	12.9	13.6	14.5	15.6	16.9	18.4
525	12.7	13.5	14.2	15.2	16.3	17.7	19.2
550	13.3	14.1	14.8	15.8	17.0	18.5	20.1
575	13.8	14.6	15.4	16.5	17.7	19.2	20.9
600	14.3	15.2	16.0	17.1	18.4	20.0	21.8
625	14.8	15.7	16.6	17.8	19.1	20.8	22.6
650	15.4	16.3	17.2	18.4	19.8	21.5	23.4
675	15.9	16.8	17.8	19.0	20.5	22.3	24.2
700	16.4	17.4	18.4	19.6	21.2	23.0	25.1
725	16.9	17.9	19.0	20.3	21.9	23.8	25.9
750	17.4	18.4	19.5	20.9	22.5	24.5	26.7
775	17.9	19.0	20.1	21.5	23.2	25.2	27.5
800	18.3	19.5	20.7	22.1	23.9	26.0	28.3



STATIC RADIAL DEFLECTION – 315/680-18x12.0J @ CA 0.0° DHB





STATIC RADIAL DEFLECTION – 315/680-18x12.0J @ CA -3.0 ° DHB

Load [kg]	Inflation Pressure [bar]						
	2.6	2.4	2.2	2.0	1.8	1.6	1.4
0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
25	1.0	1.0	1.0	1.1	1.1	1.2	1.3
50	1.9	2.0	2.1	2.1	2.2	2.4	2.5
75	2.8	2.9	3.0	3.1	3.3	3.5	3.8
100	3.7	3.8	3.9	4.1	4.3	4.6	4.9
125	4.5	4.6	4.8	5.0	5.3	5.7	6.1
150	5.3	5.5	5.7	6.0	6.3	6.7	7.2
175	6.1	6.3	6.6	6.8	7.3	7.7	8.3
200	6.8	7.0	7.4	7.7	8.2	8.7	9.4
225	7.6	7.8	8.2	8.5	9.1	9.7	10.4
250	8.3	8.5	9.0	9.4	10.0	10.6	11.5
275	9.0	9.3	9.7	10.2	10.8	11.6	12.5
300	9.7	10.0	10.5	11.0	11.7	12.5	13.5
325	10.3	10.6	11.2	11.7	12.5	13.4	14.4
350	11.0	11.3	11.9	12.5	13.3	14.2	15.4
375	11.6	12.0	12.6	13.2	14.1	15.1	16.3
400	12.2	12.6	13.3	13.9	14.9	15.9	17.3
425	12.9	13.3	13.9	14.7	15.7	16.8	18.2
450	13.5	13.9	14.6	15.4	16.4	17.6	19.1
475	14.0	14.5	15.3	16.1	17.2	18.4	20.0
500	14.6	15.1	15.9	16.7	17.9	19.2	20.8
525	15.2	15.7	16.5	17.4	18.6	20.0	21.7
550	15.8	16.3	17.1	18.1	19.3	20.7	22.5
575	16.3	16.8	17.7	18.7	20.0	21.5	23.4
600	16.9	17.4	18.3	19.3	20.7	22.3	24.2
625	17.4	17.9	18.9	20.0	21.4	23.0	25.0
650	17.9	18.5	19.5	20.6	22.1	23.7	25.8
675	18.4	19.0	20.1	21.2	22.7	24.5	26.6
700	19.0	19.6	20.6	21.8	23.4	25.2	27.4
725	19.5	20.1	21.2	22.4	24.0	25.9	28.2
750	20.0	20.6	21.8	23.0	24.7	26.6	29.0
775	20.5	21.1	22.3	23.6	25.3	27.3	29.7
800	20.9	21.6	22.8	24.2	25.9	27.9	30.5



STATIC RADIAL DEFLECTION – 315/680-18x12.0J @ CA -3.0° DHB

